MT-PRO+ PORTABLE GRAIN MOISTURE TESTER



1-800-821-9542 www.AgraTronix.com





Part No. 05100 Carrying Case - Part No. 06053 Replacement Cap - Part No. 06061



Convenient Clamshell **Packaging**



Carrying Case With Strap Included

FEATURES

- Direct readout for 40 different grain scales
- High frequency capacitive circuit with accurate temperature compensation circuit
- Illuminated, multilingual display English, French, German, Italian, Portuguese, Spanish and Swedish
- Protective carrying case with shoulder strap included

THE MT-PRO+ ADVANTAGE

- Automatically averages selectable number of tests
- Stores average calibration for all grains tested
- Direct readout for above limit and below limit values
- USB port for personalization (adding user name), grain scale, firmware and diagnostic updates
- Fewer push-buttons with standard interface configuration (up. down, left, right, enter)
- 2.5 in. LCD with selectable large or standard fonts, displays active function and allows user to scroll up/ down through the numbered grain scales
- Industry first Backlit push-button interface for low light conditions
- Battery power indicator warning at power up when battery is below 15% capacity
- Battery saver user selectable shut-down time

SPECIFICATIONS	
Moisture Range	5% - 40% depending on grain tested
Temperature Range	32° - 113° F (0° - 45° C)
Repeatability	±0.5% in normal moisture
& Accuracy	range for stored grain
Display Resolution	0.1% moisture
Battery	Two 9V batteries required

